

Circuit Diagram



定 枚

容量	7.5kVA
Capacity	

一次電圧 Primary Volt	R400/F440V
----------------------	------------

二次電流 Secondary Curr	21.7A
------------------------	-------

Class	Mass	Unit
絶縁抵抗		
Insulation Resistance		

100M Ω Min. at DC1000V

絶縁耐圧
Dielectric Withstand Volt

Dielectric withstand volt.
P-E P-S AC 60Hz 4.0kV / 1min.

S-E	AC 60Hz	2.0kV / 1min.
-----	---------	---------------


準拠規格 JEC-2200-2014

Standard

DPI DT 40 CD


SEC. PT-80 9P M5 締付トルク 2.0~3.0N・m

端子台配列 Terminals Arrangement



負荷側お客様配線(出荷時200V配線)

SEC.	u	u	u	v	v	v	w	w
	200	220		200	220		200	220



摘要 REMARKS	
------------	--



今井電機株式会社

DATE 22.11.09

M. Fujitaka
APPROVED:

N. Malurkar

三相乾式複卷變壓器
Dry type Isolating Transformer

	mm
車玉加理 FINISH	

[illegible]

MODEL

DWG.NO

NT3-Y7500-42

SN3Y75004200

改訂
Ver.